

Product Datasheet model ultravision 9301 714



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Anatomical shape and soft material allow close, yet comfortable fit * Fits comfortably over most prescription spectacles * Nose bridge works well with respirators * Frosted top to reduce glare * High-quality, easily adjustable headband * Optically correct lens (EN 166 class 1) does not distort view or cause headaches * Simple lens replacement reduces cost
<p>Technical details</p> <p>Frame</p> <p>Material Features Colour</p> <p>Material Features Colour</p>	<p>Front piece PVC ventilation system transparent light grey</p> <p>Headband synthetic headband adjustable anthracite/lime</p>

Manufacturer's ID code	Marking W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Impact resistance	F (45 m/s)
Tested acc. to DIN	DIN
No. of certificat. body	0196
Conformity symbol	CE
Lens	
Material	CA
Thickness	1,2 mm
Coating	inside antifog
Colour	clear
	Marking
Filter	2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	119 g
Packing	80 pieces in one carton
Standards	DIN EN 166 + DIN EN 170