

Technical specs

JUMPER2S3 - JUMPER2 S3 SRC

Name:

PIGMENTED SPLIT LEATHER BOOTS - S3 SRC

Size:

36 - 37 - 38 - 39 - 40 - 41 - 42 - 43 - 44 - 45 - 46 - 47

Colour:

Black



Description :

CLASSIC INDUSTRY range boots. Upper : Pigmented split leather. Lining : Polyamide Mesh. Footbed : Fixed - Polyamide on antibacterial latex. Outsole : Injected - Dual-density PU.

Safety toe-cap and anti-penetration insert : Stainless Steel.

Materials:

See description

Strong points:

Waterproof. Puncture-proof sole. Shock-resistant and crushproof toe cap (200J). Energy absorber heel. Oil resistant bottom assembly. Slip-resistant studded sole for loose soil. Anti-static protection.

Instructions for use:

Safety footwear for professional use. Footwear for general use, outdoor works (construction, second work/craftman...) or indoor works (Heavy Industry, services/logistic...).

Safety footwear S3 SRC , class I Ankle boot. Footwear with a protective toe cap providing protection against shocks equivalent to 200 joules and against crushing risks under a maximum 15 kN load, and puncture-proof sole with anti-penetration insert (P). Footwear with antistatic properties (A), energy absorbing heel (E), Water resistant upper (WRU). Slip resistant Footwear provided for indoor or outdoor use and for smooth and oily industrial-type floors (SRC). Cleated outsole, with resistance to fuel oil (FO)

Limits to use:

The DELTAPLUS® guarantee can only be applied optimal-condition shoes, being used without adding up any accessories likely to generate a change in protection, or it cannot be applied when its use is not specified in the current instructions for use. Not to be used for protection against further hazards than defined above. Not to be used within the scope of any other field of activity than that defined in the above-mentioned instructions. A insock is provided with this footwear. Testing was carried out on the footwear with the insock in place. Consequently, this footwear must be worn with the insock in place. It may only be replaced by a comparable insock supplied by Delta Plus. This footwear contains no substances known to cause allergic reactions in people with allergic sensitivities.

Instructions for storage:

To be stored in its original packing in a dry place, sheltered from sun light.

Instructions for cleaning / maintenance:

After any use, leave unpacked shoes in a ventilated place away from any heat source. To remove clay and dust, use a non metallic brush. For stains, use a wet cloth with soap if necessary. To shoe polishing, use a standard product.

Performances :

Safety footwear S3, SRC, Class I, Comply with the requirements of the European Directive 89/686, special for ergonomics, harmlessness, comfort, airing and flexibility and with the requirements of the European standards EN ISO 20344:2011 and



DELTA PLUS GROUP

La Peyrolière - B.P. 140 - 84405 APT Cedex - France
www.deltaplus.fr



Technical specs

JUMPER2S3 - JUMPER2 S3 SRC

EN ISO 20345:2011

- **EN ISO 20345:2011** Personal protective equipment - Safety footwear.
S3 : Additional special requirements
SRC : Resistance to slipping