Printing date 20.01.2015

Version number 5

Revision: 20.01.2015





Printing date 20.01.2015

Version number 5

Revision: 20.01.2015

Trade name: Karlsons Klister (Classic Tub)

(Contd. of page 1)

· Special labelling of certain preparations:

After article 10 no. 4 of DIRECTIVE 1999/45/EC it shall not be necessary to indicate the R phrases or the S phrases, if the contents of the package do not exceed 125 ml.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

 Dangerous components: 		
CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-XXXX	methyl acetate Xi R36; F R11 R66-67 ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol ▶ F R11 ♦ Flam. Liq. 2, H225	5,0-<10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX 02-2119752542-40-0000	acetone Xi R36; F R11 R66-67 ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	5,0-<10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

FU

UHU

Printing date 20.01.2015

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5

Revision: 20.01.2015

Trade name: Karlsons Klister (Classic Tub)

(Contd. of page 2)

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

79-20-9 methyl a	cetate	
AGW (Germany)	Long-term value: 610 mg/m³, 200 ppm 4(II);DFG, Y	
64-17-5 ethanol		
AGW (Germany)	Long-term value: 960 mg/m³, 500 ppm 2(II);DFG, Y	
67-64-1 acetone		
IOELV (EU)	Long-term value: 1210 mg/m³, 500 ppm	
AGW (Germany)	Long-term value: 1200 mg/m³, 500 ppm 2(I);DFG, EU	
Ingredients with	biological limit values:	
67-64-1 acetone		
BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton	
· Additional inform	nation: The lists valid during the making were used as basis.	(Contd. on pa



Printing date 20.01.2015

· Evaporation rate

water:

· Solubility in / Miscibility with

Version number 5

Revision: 20.01.2015

(Contd. of page 3)

Trade name: Karlsons Klister (Classic Tub)

8.2 Exposure controls				
Personal protective equipment:				
General protective and hygienic n				
The usual precautionary measures are to be adhered to when handling chemicals. Do not inhale gases / fumes / aerosols. • Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the				
			preparation.	
				onsideration of the penetration times, rates of diffusion and th
degradation				
of quality and varies from manufacture substances, the resistance of the therefore to be checked prior to the a				
Penetration time of glove material				
	be found out by the manufacturer of the protective gloves an			
has to be observed. Eye protection: Not required.				
Lye protection: Not required.				
SECTION OF Physical and a	amical proportion			
SECTION 9: Physical and ch	iemical properties			
9.1 Information on basic physical	and chemical properties			
General Information				
Appearance:				
Form:	Fluid			
Colour:	Colourless			
Odour:	Ester-like			
Odour threshold:	Not determined.			
pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	55 °C			
Flash point:	-13 °C			
Flammability (solid, gaseous):	Not applicable.			
Ignition temperature:	425 °C			
Decomposition temperature:	Not determined.			
Self-igniting:	Product is not selfigniting.			
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.			
Explosion limits:				
Lower:	3,1 Vol %			
Upper:	16,0 Vol %			
Vapour pressure at 20 °C:	220 hPa			
Density at 20 °C:	0,99 g/cm ³			
Relative density	Not determined.			
Vapour density	Not determined.			
Evanoration rate	Not determined			

Not determined.

Fully miscible.



Printing date 20.01.2015

Version number 5

Revision: 20.01.2015

Trade name: Karlsons Klister (Classic Tub)

	(Contd. c	of page 4
Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic at 20 °C:	4400 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	65,9 %	
Water:	0,4 %	
VOC (EC)	65,85 %	
Solids content:	33,8 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

Acute toxicity:

· LD/LC50 values relevant for classification:

79-20-9 methyl acetate

Oral LD50 3705 mg/kg (rabbit)

64-17-5 ethanol

		7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

Innalative	LC50/4 N	200

67-64-1 acetone

5800 mg/kg (rat) Oral LD50 LD50 20000 mg/kg (rabbit) Dermal

· Primary irritant effect:

- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.

SECTION 12: Ecological information

12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 6)

EU



Printing date 20.01.2015

Version number 5

Revision: 20.01.2015

(Contd. of page 5)

Trade name: Karlsons Klister (Classic Tub)

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1133
 14.2 UN proper shipping name ADR IMDG, IATA 	1133 KLEBSTOFFE, Sondervorschrift 640H ADHESIVES
 14.3 Transport hazard class(es) 	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>
 14.5 Environmental hazards: Marine pollutant: 	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
 Danger code (Kemler): EMS Number: 	33 F-E,S-E
• 14.7 Transport in bulk according to Anne	
of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) 	5L
	(Contd. on page 7)



Printing date 20.01.2015

Version number 5

Revision: 20.01.2015

Trade name: Karlsons Klister (Classic Tub)

	(Contd. of page 6)
 Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
 Tunnel restriction code 	D/E
· IMDG	
· Limited quantities (LQ)	5L
• Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1133, ADHESIVES, special provision 640H, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: CRD
- · Contact:
- Frau A. Liar.

Herr Dr. C. Hanf

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

- STOT SE 3: Specific target organ toxicity Single exposure, Hazard Category 3
- * * Data compared to the previous version altered.