

## PRODUCT INFORMATION

### **tesa Stick & tesa Easy Stick ecoLogo®**

#### **Product Description/ Application:**

- Glues paper, cardboard, photos.
- Fast, clean and smooth paper gluing
- Solvent free
- Can be washed out with cold water
- Easy to apply, also on large areas.
- The triangular shape of the tesa Easy Stick ecoLogo® allows precise gluing into corners and along edges.
- The corners of the tesa Easy Stick ecoLogo® are regenerated when the glue is retracted.
- They are especially handy for quick gluing jobs in the office, studio, workshop, school and nursery.

#### **Preparation**

- Surfaces to be glued should be clean, dry and grease-free.

#### **Usage**

- Push-on cap is easy to remove.
- Twist the glue stick out only as far as needed.
- Apply glue thinly and evenly to one surface.
- Immediately after application, press surfaces together.
- After use, make sure the stick is closed properly.
- Up to 4mm of projecting glue need not be retracted.

#### **Ecological features**

- Solvent free
- 60% natural materials (water)
- Housing/plastic parts: 100% recycled plastic
- Trays: 80% recycled cardboard

#### **Dimensions:**

tesa Stick ecoLogo®	10g, 20g, 40g
tesa Easy Stick ecoLogo®	12g , 25g

#### **Technical Data: (mean values)**

Base	Plastomer, PVP
Consistency	Firm gel
Appearance	White
Storage	Approx. 2 years after opening at room temp.18-25°C. Store in a dry place.
Material Stick Housing	Recycled PP/PE
Material Packaging	Cardboard, PS (Tray)

**tesa SE**  
Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

<http://www.tesa.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.